# **CELEBRATION™** LIGHTED MIRROR

Hospitality Performance Specification



The Celebration™ Lighted Mirror illuminates the bathroom and vanity area with dual sources of natural light while the modern wood frame makes this a beautiful addition to contemporary decor.

# THERE'S ONLY ONE ELECTRIC MIRROR™

Electric Mirror is the global leader in lighted mirrors and Mirror TV technology. With unparalleled customer service and amazing innovation, Electric Mirror is the standard of luxury for five-star hotels, upscale commercial projects and designer homes.

# **FEATURES**

- Elife<sup>™</sup>-8 Years extended lamp replacement cycle
- Brilliant chassis design for increased light output
- EnergyLite™-Half the energy with equal light output\*
- · Wood urban profile frame in espresso, beachwood, cherry, or walnut finish
- Natural light color ideal for makeup application
- HardCoat<sup>™</sup> anti-corrosion mirror treatment
- Rust resistant powder coated metal construction
- Environmentally sustainable and energy efficient
- Proudly made in the USA
- Patented (US D579,671)
- · Stainless steel hanger
- Welded Construction

#### LIGHTING

- Low-Mercury T5HO warm fluorescent (US Made)
- CRI 85
- CCT (K) 3000
- Average lamp life of 35,000 hours
- 50,000 cycle ballast

#### **OPTIONS**

- Diamond Clear<sup>™</sup> extra white mirror
- Dimmable Separate wall control required
- Defogger
- Night Light
- Add TV (See Celebration<sup>™</sup> Lighted Mirror TV)
- Alternative framing options (See frame specifications)
- Custom Sizes
- Glass Shelf
- LED Digital Clock
- LED Lighting

# **SAFETY**

- Tested to UL/UL-C 1598 including section 16.23 (adhesive support test)
- International Certifications
- · Safety backed mirror

\*Effective 2013




# **CELEBRATION™** LIGHTED MIRROR Hospitality Performance Specification


#### **SPECIFICATION**


- The top of the lighted mirror above the bathroom vanity should be a minimum of 6' 6" above the finished floor.
- Electrical connections made with MC cable brought through the chassis knockout, no electrical box required.
- Electrical power should be controlled by a light switch.
- Fixture should be mounted to wall studs to provide sufficient support. Mounting holes are provided in the chassis.


MODEL NUMBER	DIMENSIONS	POWER REQUIREMENTS	LAMPING
CEB-MU0□-29.00x41.00	29" W x 41" H x 2.5" D 737mm x 1,041mm x 63.5mm	120 - 277 VAC, .4336 Amps, 48W	2 x T5HO, 24W
CEB-MU0 <sub>-41.00x41.00</sub>	41" W x 41" H x 2.5" D 1,041mm x 1,041mm x 63.5mm	120 - 277 VAC, .6528 Amps, 78W	2 x T5HO, 39W
CEB-MU0□-53.00x41.00	53" W x 41" H x 2.5" D 1,346mm x 1,041mm x 63.5mm	120 - 277 VAC, 1.356 Amps, 108W	2 x T5HO, 54W
CEB-MU0□-65.00x41.00	65" W x 41" H x 2.5" D 1,651mm x 1,041mm x 63.5mm	120 - 277 VAC, 1.3357 Amps, 160W	2 x T5HO, 80W


☐- Indicates finish selection, see frame specification for details











**PROPRIETARY AND CONFIDENTIAL:** The information contained in this specification is the sole property of Electric Mirror\*.

Any reproduction in part or in whole without written permission from Electric Mirror\* is prohibited.

--© 2012 ELECTRIC MIRROR®