


All bathtub dimensions are  $\pm 1/2"$ .

### Airbath System II



#### LEGEND:



BLOWER



ON/OFF CONTROL

— ACCESS PANEL (BUILT IN)

#### STANDARD EQUIPMENT:

- Integral Waste & Overflow  
Available in: Polished Chrome, Polished Brass, Polished Nickel, Satin Nickel, Oil Rubbed Bronze

#### INSTALLATION TIPS

- Install according to Owner's Manual and local codes.
- Access panel for Airbath® systems included with the Contura III series.
- Hot water supply should be 65-75% of tub capacity or greater. Always consult your local plumber for recommendations as installations will vary.

#### DIMENSIONS:

60" x 32" x 23" (1524 x 813 x 584 mm)

Gallon to Overflow = 60 (Liters = 227)

Factory installed integral drain.

**TUB FLOOR:** Non-Textured

**UNDERMOUNT:** No

**AVAILABLE COLORS:** White and Biscuit

#### ELECTRICAL REQUIREMENTS

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

#### OPTIONAL ACCESSORIES

- Chromotherapy
- Remote Control Upgrade

#### CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories - Canada (cUL)
- Canadian Standards Association - (CSA)
- ANSI Z124.1 • ANSI A112-19.7 • ANSI A112.19.8

Contact Americh for additional approvals.