



KEY BENEFITS

Absolute comfort, absolutely unique look
Refined ergonomic design with extra-wide armrests
Convenient integrated seat

STANDARD FEATURE(S)

Ergonomic backrests
Inclined armrests
White or Biscuit cushion
Integrated seat
Two 12-inch grab bars

PLUMBER FEATURE(S)

Drop-in corner installation or with apron

COMMON OPTIONS

Acrylic apron
Flexible Main Hose 15 ft for Electronic Control
Metal trim kit
Metal trim kit for Aerofeel only
[One chromatherapy light](#)
Ozonator whirlpool system
Thermo-Acoustic system

Tiling flange

Two 12-in. metal grab bars

Waste and overflow

Water heater assembly

MASSAGE SYSTEM(S)


[Aerofeel](#)

Combined Hydromax and Aerofeel

[Hydromax](#)

Hydromax Rest™

Hydromax with Backmax



Codes/Standards Applicable

- ANSI Z124.1.2
- CSA B45 Series

Whirlpool Bathtubs:

- UL1795
- ASME A112.19.7
- CSA C22.2 No. 218.2
- CSA B45.10

Colors

Standard Acrylic Colors







☐

☐

☐

White 001

Bone
(Natural) 004

Biscuit
(Silk/Linen)
007

Non-Standard Acrylic Colors

















☐

☐

☐

☐

☐

☐

☐

☐

Almond 013

Sterling
Silver (Gray)
005

Platinum
Gray 009

Black 015

Ice Gray 016

Fawn Beige
054

Innocent
Blush 066

Sandbar 143

Colors shown are for reference purposes only and are subject to change without notice. Exact matches are not possible with your monitor display or printing method used.

Model Specifications, Options and Accessories

☒

No	Model	Dimensions in. (mm)	Approx. Weight lb (kg)	PKG ft3 (m3)
☐ 100055-000	BATHTUB	60 X 60 X 19 7/8	92	49
☐ 100201-000	Removable acrylic apron	84 5/8 X 3 X 18 1/4	30	20
Water Capacity: Minimum: 48 gal. Maximum: 56 gal.				

Whirlpool Systems

☒

No	Description	Dimensions in. (mm)	Approx. Weight lb (kg)	PKG ft3 (m3)
☐ 100055-004	HYDROMAX WITH BACKMAX White or Biscuit cushion included	60 X 60 X 19 7/8	137	49
☐ OPT 20141	HYDROMAX REST™	N/A	N/A	N/A

Air System

☒

No	Description	Dimensions in. (mm)	Approx. Weight lb (kg)	PKG ft3 (m3)
☐ 100055-055	AEROFEEL	60 X 60 X 19 7/8	117	49

Combined Systems

☒

No	Description	Dimensions in. (mm)	Approx. Weight lb (kg)	PKG ft3 (m3)
☐ 100055-094	COMBINED HYDROMAX AND AEROFEEL	60 X 60 X 19 7/8	152	49
☐ OPT 20141	HYDROMAX REST™	N/A	N/A	N/A

Common Options

☒	No	Description	Dimensions in. (mm)	Approx. Weight lb (kg)	PKG ft3 (m3)
☐	OPT 10053	One chromatherapy light (factory installed)	2 3/8	2.5	N/A
☐	OPT 10096	Thermo-Acoustic system (minimal installation required).	N/A	6	
☐	OPT 10097-084	Two 12-in. metal grab bars available in other colors (factory installed) Available colors: Chrome (084), Polished Brass (085) and Brushed Nickel (105)	12	2.5	
☐	OPT 10097-085				
☐	OPT 10097-105				
☐	OPT 20140-001	Waste and overflow (factory installed) Available colors: White (001), Bone (004), Biscuit (007), Chrome (084), Polished Bras (085) and Brushed Nickel (105)	N/A	N/A	
☐	OPT 20140-004				
☐	OPT 20140-084				
☐	OPT 20140-085				
☐	OPT 20140-105				

Whirlpool Options

✓	No	Description	Dimensions in. (mm)	Approx. Weight lb (kg)	PKG ft3 (m3)
☐	OPT 10095	Water heater assembly (factory installed)	9 X 5 X 3	2	N/A
☐	OPT 10106-084	Metal trim kit for whirlpools and combined systems (factory installed) Available colors: Chrome (084), Polished Brass (085) and Brushed Nickel (105)	N/A	1.5	
☐	OPT 10106-085				
☐	OPT 10106-105				
☐	OPT 20139	Ozonator whirlpool system		N/A	

Air System Options

☒	No	Description	Dimensions in. (mm)	Approx. Weight lb (kg)	PKG ft3 (m3)
☐	OPT 10119-084	Metal trim kit for Aerofeel only electronic control (factory installed) Available colors: Chrome (084), Polished Brass (085) and Brushed Nickel (105)	N/A	1.5	N/A
☐	OPT 10119-085				
☐	OPT 10119-105				

Accessories

✓	No	Description	Dimensions in. (mm)	Approx. Weight lb (kg)	PKG ft3 (m3)
☐	10006920	Tiling flange (sold separately)	2 x 60	1.5	N/A
☐	10019708	Flexible Main Hose (15-ft. extension) for Electronic Control Air Massage - Kit (sold separately)	N/A	2.5	0.89
☐	10025081-001	Waste and overflow (sold separately) Available colors: White (001), Bone (004), Biscuit (007), Chrome (084), Polished Bras (085) and Brushed Nickel (105)		N/A	N/A
☐	10025081-004				
☐	10025081-007				
☐	10025081-084				
☐	10025081-085				
☐	10025081-105				

Canada	Alberta British Columbia Manitoba New Brunswick Newfoundland Nova Scotia Northwest Territories Ontario Prince Edward Island Quebec Saskatchewan Yukon Territory
United States	Alabama Alaska Arizona Arkansas California Colorado Connecticut Delaware District of Columbia Florida Georgia Hawaii Idaho Illinois Indiana Iowa Kansas Kentucky Louisiana Maine Maryland Massachusetts Michigan Minnesota Mississippi Missouri Montana Nebraska Nevada New Hampshire New Jersey New Mexico New York North Carolina North Dakota Ohio Oklahoma Oregon Pennsylvania Rhode Island South Carolina South Dakota Tennessee Texas Utah Vermont Virginia Washington West Virginia Wisconsin Wyoming
International	Jamaica Switzerland Korea China Taiwan Pilipinas Vietnam Malaysia Singapore Egypt Kuwait Dubai Qatar Saudi Arabia Bermuda Turks & Caicos Dominican Republic Panama Costa Rica Guatemala Colombia

Here are the electrical specifications for all MAAX Collection bathtub therapeutic systems offered in the United States.

PLEASE NOTE THAT SOME SYSTEMS MAY NOT BE AVAILABLE ON THE PRODUCT YOU HAVE SELECTED.

Please refer to the *Common Options* and *Massage System(s)* sections for more details.

HYDROFEEL	
Pump: Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with these two options: Chromatherapy and Ambiance Set (Urban® Water Cascade)	
Heater: Requires a dedicated circuit protected by a Class A GFCI.	
Pump	1.5HP / 120V / 12.5A / 60Hz
REST™ Pump Option	1HP / 120V / 9.4A / 60Hz
Heater	1500W / 120V / 12.5A / 60Hz

HYDROMAX	
Pump: Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with Chromatherapy (option).	
Pump 2 (for large bathtubs): Requires a dedicated circuit protected by a Class A GFCI.	
Heater: Requires a dedicated circuit protected by a Class A GFCI.	
Pump	1.5HP / 120V / 12.5A / 60Hz
REST™ Pump Option	1HP / 120V / 9.4A / 60Hz
Heater	1500W / 120V / 12.5A / 60Hz

AEROFEEL	
Blower: Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with these two options: Chromatherapy and Ambiance Set (Urban® Water Cascade).	
Blower	1.4HP / 120V / 9.5A / 60Hz

COMBINED HYDROFEEL / AEROFEEL	
Blower: Requires a dedicated circuit protected by a Class A GFCI.	
Pump: Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with these two options: Chromatherapy and Ambiance Set (Urban® Water Cascade).	
Heater: Requires a dedicated circuit protected by a Class A GFCI.	
Blower	1.4HP / 120V / 9.5A / 60Hz
Pump	1.5HP / 120V / 12.5A / 60Hz
REST™ Pump Option	1HP / 120V / 9.4A / 60Hz
Heater	1500W / 120V / 12.5A / 60Hz

COMBINED HYDROMAX / AEROFEEL	
Blower: Requires a dedicated circuit protected by a Class A GFCI.	
Pump: Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with Chromatherapy (option).	
Pump 2 (for large bathtubs): Requires a dedicated circuit protected by a Class A GFCI.	
Heater: Requires a dedicated circuit protected by a Class A GFCI.	
Blower	1.4HP / 120V / 9.5A / 60Hz
Pump	1.5HP / 120V / 12.5A / 60Hz
REST™ Pump Option	1HP / 120V / 9.4A / 60Hz
Heater	1500W / 120V / 12.5A / 60Hz

CHROMATHERAPY	
Requires a dedicated circuit protected by a Class A GFCI.	

AMBIANCE SET (URBAN® WATER CASCADE)	
Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with Chromatherapy (option).	

Installation Note

Install this product according to the *Installation Guide*.

All electrical wiring must be done per national/local electrical codes.