
FINITY 9



SERIES MODEL # AI9INF6636




No alternate pump location available.



*Available without fast-fill waterfall spout.








A deck must be built around the tub.

NOTE: Please allow for plumbing to extend approx. 3" beyond tub rim.



Rough-In Plumbing Measurements 8 3/4"

SPECIFICATIONS:

GENERAL SPECIFICATIONS:

Tub Size 66" x 34 1/2" x 31 1/2"

168 cm x 88 cm x 78 cm **Bathing Well** 40 1/2" long

21" wide

22 1/2" interior depth

Maximum Water Depth

Shipping Weight 289 lbs. / 131 kg **Tub Weight Filled** 931 lbs. / 406 kg **Tub Only Weight** 192 lbs. / 87 kg Gallons to Overflow 89 gal. / 336 L Gallons to Operate 65 gal. / 246 L

ELECTRICAL SPECIFICATIONS:

2 HP: 12 AMP: 110V Pump Inline Heater 1.5 kW: 12.5 AMP: 110V

Requirement 1-15 AMP 2 pole, separate circuit

required protected with Class A GFCI

1 HP; 10.5 AMP; 110V **Blower**

Requirement 1-15 AMP 1 pole, separate circuit

required protected with Class A GFCI

This whirlpool will need to be hard wired to the breaker box. Three outlets will be supplied on the whirlpool.

This unit is not recommended for shower installations.

This unit has a 3/4" female waterfall fill spout connection.

Fax-On-Demand Document # 1165



STANDARD EQUIPMENT:

16 Hydrotherapy Jets including:

- 12 Shiatsu Back Jets
- 2 Rotary Massage Foot Jets
- 2 Full Size Pressure-Flo Hydrotherapy Jets

Air Bath System:

- 1 HP Variable Speed Air Blower with 20-Minute Timer
- Electronic Control Panel
- Automatic Purge and Dry Cycle - 600 Watt Air Heating System **Aquatic Quality Features:**

- 2 HP Run-Dry Pump
- 1.5 kW Inline Maintenance Heater
- "Quiet Pad" Anti-Vibration Pump Mount for Quiet Pump Operation
- Shiatsu Electronic Control Panel with Preprogrammed Jet Sequencer
- Bath-Side Electronic Control Panel with Temperature Display
- Pulsating Neck Jet Pillow
- Reclining Lounge Seat and 2 Arm Rests
- Integrally Molded Fast-Fill Waterfall Spout/Optional
- please specify on order (valves not included)
- Chromatherapy
- Slip Resistant Floor
- Adjusta-Level Base
- Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
- Durable, Easy to Clean, Lucite® Cast Acrylic Surface
- Available in 8 Standard No-Charge Colors

UL & IAPMO Listed. Factory Tested Limited Lifetime Warranty

OPTIONAL EQUIPMENT:

- Available without Fast-Fill Waterfall Spout - See Price List for Details
- Comfort Pillow -- Oval or Rectangle
- Bolt-On Grab Bar
 - White, Biscuit, Chrome, Polished Brass, Satin Nickel, Polished Nickel, Oil Rubbed Bronze or Gold
- Jet Finish
- Chrome, Polished Brass, Gold, Polished Nickel, or Satin Nickel
- Lift & Turn Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel. Satin Nickel or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel Satin Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- Hand Held Jet Chrome or Polished Brass
- Premium Colors

All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.

The manufacturer accepts a 1/4" variance. There are variations on each tub and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building should be measured from the tub; Aquatic Industries, Inc. assumes no responsibility for preparatory work. www.aguaticwhirlpools.com 800.555.5324