







Tub pictured with optional waste & overflow.




All bathtub dimensions are $\pm 1/2$ ".

Builder Series



Luxury Series




Platinum Series


N/A

Combination

(pump and blower location only)




Airbath System II



Airbath System III

N/A



INSTALLATION TIPS

- Install according to Owner's Manual and local codes.
- Any whirlpool or Airbath® unit requires an access panel.
- Hot water supply should be 65-75% of tub capacity or greater. Always consult your local plumber for recommendations as installations will vary.

DIMENSIONS

60" x 32" x 18" (1524 x 813 x 457 mm)

Whirlpool Operating Gallons = 45 (Liters = 170)

Gallon to Overflow = 55 (Liters = 208)

TUB FLOOR: Textured

UNDERMOUNT: No

ELECTRICAL REQUIREMENTS

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

STANDARD EQUIPMENT:

- Apron
- Molded Tile Flange

OPTIONAL ACCESSORIES

- Chromotherapy
- Grab Bars: 9" - 14" - 16"
- High Density Insulation
- Inline Heater
- Jets: Additional or Rotary
- Pillows: 13"
- Quiet Pump with Built-in Heater Upgrade
- Remote Control Upgrade (Select Series Only)
- Trim Kit Upgrade
- Waste & Overflow

CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories - Canada (cUL)
- Canadian Standards Association - (CSA)
- ANSI Z124.1 • ANSI A112-19.7
- ANSI A112.19.8 • ASTM F462-79

Contact Americh for additional approvals.