

LF1062 SPECIFICATIONS

HALO FREESTANDING TOILET

FEATURES:

- Streamlined, seamless one piece HET design
- Stylish toilet with 12" (305mm) rough-in
- Vitreous china
- HET Low consumption 1.28 gpf / 4.8 lpf siphon jet flushing action
- Single push button flush activation
- Elongated bowl, with large water surface
- Skirted styling with concealed trapway for easy cleaning
- Includes tank cover, fittings, chrome trip lever, mounting covers and thermoplast soft close seat with quick release for easy cleaning
- Powerful, quiet flush every time
- Standard two-bolt installation system
- Includes polished chrome push button flush actuator

SPECIFICATIONS:

Water Use:	1.28 gpf (4.8 lpf)
Flush System:	Siphon jet gravity feed
Min. Water Pressure:	8 psi
Water Surface:	11½" x 9½" (292mm x 241mm)*
Trap Diameter:	2½" (54mm)*
Rough In:	12" (305mm)*
Trap Seal:	2½" (64mm)*
Warranty:	One Year Limited Warranty
Material:	Tank & Bowl: Vitreous China
Shipping Weight:	112 lbs. (51kg)*
Shipping Dimensions:	(LWH) 30" x 16" x 30" (762mm x 406mm x 762mm)*

FINISHES:

White

CODES / STANDARDS APPLICABLE:

- Meets or exceeds ANSI / ASME standard A112.19.2 and CAN / CSA B 45 requirements
- ASME A112.19.2.2003
- IAPMO / UPC / cUPC
- ASME A112.19.5-2005 / CSA B125.3-2005
- CSA B45.0
- CSA B45.1

INSTALLATION NOTES:

The rough-in must be a minimum of 12" (305mm) or more from the base of the wall or baseboard. The toilet will not fit correctly if there is less than 12" of clear space between the base of the wall / baseboard and the centreline of the outlet. Install or relocate the supply and outlet as necessary to conform to rough-in dimensions.

If a baseboard causes the rough-in to be less than 12" (305mm), it must be cut or removed to allow space for the toilet. Install this product according to the installation guide.

*Approximate measurements for comparison only.

Note: These dimensions and specifications are subject to change without notice.

