


All bathtub dimensions are $\pm 1/2"$.

Airbath System II



LEGEND:



BLOWER



ON/OFF CONTROL



ACCESS PANEL (BUILT IN)

STANDARD EQUIPMENT:

- Integral Waste & Overflow
- Available in: Polished Chrome, Polished Brass, Polished Nickel, Satin Nickel, Oil Rubbed Bronze

INSTALLATION TIPS

- Install according to Owner's Manual and local codes.
- Access panel for Airbath® systems included with the Contura II series.
- Hot water supply should be 65-75% of tub capacity or greater. Always consult your local plumber for recommendations as installations will vary.

DIMENSIONS:

66" x 32" x 24" (1676 x 813 x 610 mm)

Gallon to Overflow = 68 (Liters = 257)

Factory installed integral drain.

TUB FLOOR: Non-Textured

UNDERMOUNT: No

AVAILABLE COLORS: White and Biscuit

ELECTRICAL REQUIREMENTS

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

OPTIONAL ACCESSORIES

- Chromotherapy
- Remote Control Upgrade

CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories - Canada (cUL)
- Canadian Standards Association - (CSA)
- ANSI Z124.1 • ANSI A112-19.7 • ANSI A112.19.8

Contact Americh for additional approvals.